

Ordering code

CPR6900 radar level transmitter with thread version antenna



CPR6900									
	1	2	3	4	5	6	7	8	9

1 | LANGUAGE

A	English
I	Chinese
S	Spanish
T	Customized

2 | APPROVAL

XX	Standard
CX	Ex ia IIC T6 Ga
DX	Ex d ia [iaGa]IIC T6/T2 Gb
EX	Ex iaD tD A21 IP67T80°C/T290°C
TT	Customized

3 | ANTENNA VERSION/MATERIAL

T	Thread with integrated horn antenna 316L+PTFE
V	Thread with integrated horn antenna/316L+PEEK

4 | PROCESS FITTING

TG	Thread G1½
TH	Thread G3
TD	Thread NPT1½
TI	Thread NPT3
TT	Customized

5 | SEALING MATERIAL/TEMPERATURE/PRESSURE

A	FKM/-40...+130°C/-1...20bar
B	FKM/-40...+200°C/-1...20bar
F	EPDM/-40...+130°C/-1...20bar
R	KALREZ 6230/-15...+130°C/-1...20bar
S	KALREZ 6230/-15...+200°C/-1...20bar
G	KALREZ 6375/-15...+130°C/-1...20bar
H	KALREZ 6375/-15...+200°C/-1...20bar
T	Customized

6 | ELECTRONICS

H	Two-wire 4...20mA/HART; 24 VDC
B	Four wire 4...20mA/HART; 220 VAC
I	Four wire 4...20mA/HART; 24 VDC
W	Wireless; GPRS; Wireless C Mesh
T	Customized

7 | HOUSING/PROTECTION

A	Single chamber/ Aluminum / IP67
B	Double chamber/ Aluminum / IP67
U	Single chamber/ 316L SS/ IP67
W	Double chamber/ 316L SS/ IP67

8 | CABLE ENTRY / CABLE GLAND / CONNECT CABLE

M	M20x1.5 / with/ without
N	½NPT/ without/ without

9 | LCD DISPLAY

X	Without display
A	With display